

MINI MODEL



Standard Technical Data:

- 1 ton capacity
- Trailer or truck-mount models available
- 80,000 BTU propane fuel source
- Automatic temperature control
- 12-volt battery
- Vinyl tarp cover
- Propane tank mounting bracket (propane tank not included)
- 10 gauge capping channel and corner molding add structural integrity to the hopper preventing it from becoming out of square
- Triple wall construction
- Hopper - fully insulated
- Floor and all four walls are heated
- Trailer model with electric brakes and safety breakaway
- Rectangular tubing trailer frame
- 5-bolt wheels
- Leaf spring trailer axle
- Fork pockets for mobility
- All wiring external to hopper
- Paint: sandblasted with two coats of epoxy primer and urethane finish
- FMCSA and NATM compliant
- Operating controls located on curbside whenever possible

Trailer Measurements:

- Total length: 8' 6"
- Hopper length: 45"
- Hopper width: 40"
- Width from fender to fender: 57"
- Width of frame: 36"
- Overall height: 55"
- Shoveling platform height: 29"
- Height from top of frame to ground: 21"

Trailer Weight:

- Weight without asphalt: 945 lbs.
- Weight with asphalt: 2,945 lbs.
- GVWR: 3,500 lbs.

Truck-Mount Measurements:

- Total length: 86"
- Length without shoveling apron: 77"
- Hopper width: 40"
- Total width: 48"
- Width of frame: 36"
- Overall height: 39"

Truck-Mount Weight:

- Weight without asphalt: 695 lbs.
- Weight with asphalt: 2,695 lbs.